

Developer manual

(ONVIF Client Library)

Happytimesoft Technology Co., LTD

Declaration

All rights reserved. No part of this publication may be excerpted, reproduced, translated, annotated or edited, in any form or by any means, without the prior written permission of the copyright owner.

Since the product version upgrade or other reasons, this manual will subsequently be updated. Unless otherwise agreed, this manual only as a guide, this manual all statements, information, recommendations do not constitute any express or implied warranties.

www.happytimesoft.com

Table of Contents

Chapter 1 Build.....	4
1. 1 Dependent libraries.....	4
1. 2 Windows Platform.....	4
1. 3 Linux Platform.....	4
1. 4 Android Platform.....	4
1. 5 MAC Platform.....	4
1. 6 IOS Platform.....	4
1. 7 Embedded Platform.....	5
1. 8 Compilation parameter	5
Chapter 2 Data Structure.....	6
2. 1 ONVIF_DEVICE.....	6
2. 2 Other Data structure.....	7
2. 3 Request Data structure.....	7
2. 4 Response Data structure.....	7
Chapter 3 ONVIF Version	8
Chapter 4 API Interface.....	9
4. 1 Device discovery API	9
4. 2 ONVIF Event API	10
4. 3 System API	11
4. 4 ONVIF Client API	13
Chapter 5 Example	14

Chapter 1 Build

1.1 Dependent libraries

If you enable HTTPS function, please first compile and install OPENSSL library.

The download link:

<https://www.openssl.org/source/openssl-1.1.1g.tar.gz>

1.2 Windows Platform

Use VS2019 open OnvifClientLibrary.sln to build.

1.3 Linux Platform

```
cd OnvifClientLibrary  
make clean  
make (Compile the dynamic library)  
make -f static.mk clean  
make -f static.mk (Compile the static library)
```

1.4 Android Platform

```
cd OnvifClientLibrary  
make -f android.mk clean  
make -f android.mk  
Note : Need to install android build environment  
use QtCreator open android.pro to build  
Note : QT 5.8.0 or later for android needs to be installed
```

1.5 MAC Platform

```
cd OnvifClientLibrary  
make -f mac.mk clean  
make -f mac.mk
```

1.6 IOS Platform

```
cd OnvifClientLibrary  
make -f ios.mk clean  
make -f ios.mk  
Or use QtCreator open ios.pro to build  
Note : QT 5.8.0 or later for IOS needs to be installed
```

1.7 Embedded Platform

Modify Makefile to specify cross-compiler, then make.

1.8 Compilation parameter

PROFILE_C_SUPPORT : Implementing ONVIF profile C related interfaces

Include onvif ACCESSCONTROL, DOORCONTROL service

PROFILE_G_SUPPORT : Implementing ONVIF profile G related interfaces

include onvif RECORDING, SEARCH, REPLAY services

THERMAL_SUPPORT : Implementing ONVIF thermal service interfaces

CREDENTIAL_SUPPORT : Implementing ONVIF credential service interfaces

ACCESS_RULES : Implementing ONVIF accessrules service interfaces

SCHEDULE_SUPPORT : Implementing ONVIF schedule service interfaces

RECEIVER_SUPPORT : Implementing ONVIF receiver service interfaces

IPFILTER_SUPPORT : Implementing IP filter interfaces

DEVICEIO_SUPPORT : Implementing ONVIF deviceio service interfaces

PROVISIONING_SUPPORT : Implementing ONVIF provisioning service interfaces

Chapter 2 Data Structure

2.1 ONVIF_DEVICE

The ONVIF_DEVICE structure used to store the device configuration parameters.

```
typedef struct
{
    unsigned int local_ip;           // local ip address to connect to server, network byte
order

    DEVICE_BINFO     binfo;         // device basic information

    // request
    char            username[32]; // login user name, set by user
    char            password[32]; // login password, set by user

    BOOL           authFailed;    // when login auth failed, set by onvif stack

    ONVIF_Profile * curProfile;   // current profile pointer, the default pointer the first
profile, user can set it

    ****

    ONVIF_VideoSource * video_src;          // the list of video source
    ONVIF
```

```

    ONVIF_EVENT events;           // event information
    onvif_DeviceInformation DeviceInformation; // device information
    onvif_Capabilities Capabilities; // device capabilities
} ONVIF_DEVICE;

```

Field	Description
local_ip	local ip address to connect to server, network byte order
binfo	device basic information
username	login user name, set by user
password	login password, set by user
authFailed	when login auth failed, set by onvif stack
curProfile	current profile pointer, the default pointer the first profile, user can set it
video_src	Video source list
audio_src	Audio source list
profiles	Media profiles list
video_src_cfg	Video source configurations list
audio_src_cfg	Audio source configurations list
video_enc	Video encoder list
audio_enc	Audio encoder list
ptznodes	PTZ nodes list
ptz_cfg	PTZ configurations list
events	Onvif event message
DeviceInformation	Device information
Capabilities	Device capabilities

2. 2 Other Data structure

Other ONVIF standard data structure, please refer onvif_cm.h file

2. 3 Request Data structure

ONVIF request data structure, please refer onvif_req.h file

2. 4 Response Data structure

ONVIF response data structure, please refer onvif_res.h file

Chapter 3 ONVIF Version

The onvif client library implements the following ONVIF service:

ONVIF Service	Prefix	Url	version
device	tds	http://www.onvif.org/ver10/device/wsdl	23.06
event	tev	http://www.onvif.org/ver10/events/wsdl	22.06
media	trt	http://www.onvif.org/ver10/media/wsdl	21.12
media 2	tr2	http://www.onvif.org/ver20/media/wsdl	23.06
ptz	tptz	http://www.onvif.org/ver20/ptz/wsdl	22.12
image	timg	http://www.onvif.org/ver20/imaging/wsdl	22.06
analytics	tan	http://www.onvif.org/ver20/analytics/wsdl	22.06
recording control	trc	http://www.onvif.org/ver10/recording/wsdl	23.06
search	tse	http://www.onvif.org/ver10/search/wsdl	22.06
replay	trp	http://www.onvif.org/ver10/replay/wsdl	21.12
access control	tac	http://www.onvif.org/ver10/accesscontrol/wsdl	21.06
door control	tdc	http://www.onvif.org/ver10/doorcontrol/wsdl	21.06
device IO	tmd	http://www.onvif.org/ver10/deviceIO/wsdl	22.06
thermal	tth	http://www.onvif.org/ver10/thermal/wsdl	22.06
credential	tcr	http://www.onvif.org/ver10/credential/wsdl	21.06
access rules	tar	http://www.onvif.org/ver10/accessrules/wsdl	19.06
schedule	tsc	http://www.onvif.org/ver10/schedule/wsdl	18.12
receiver	trv	http://www.onvif.org/ver10/receiver/wsdl	21.12
provisioning	tpv	http://www.onvif.org/ver10/provisioning/wsdl	18.12

Chapter 4 API Interface

4.1 Device discovery API

The device discovery API in onvif_probe.h file.

1. int **start_probe**(const char * ip, int interval)

desc: start device discovery thread

params:

ip: start device discovery thread on the specify ip address, it can be NULL,
if ip is NULL, it will use the default ip.

interval: probe interval, unit is second, default is 30s

return: 0-success, -1-failed

2. void **stop_probe()**

desc: stop device discovery thread

3. void **set_probe_interval**(int interval)

desc: set probe interval

params:

interval: probe interval, unit is second, default is 30s, if the interval
less than 10, will be set to 30.

4. void **send_probe_req()**

desc: send probe request. the device discovery thread will automatically send
a PROBE request at the specified interval. Calling this interface will immediately
send a PROBE request.

5. void **set_probe_cb**(onvif_probe_cb cb, void * pdata)

desc: set device probed callback function

params:

cb: the callback function point

pdata: user data, when call backback pass back to user.

The callback function prototype is as follows:

```

void (* onvif_probe_cb)(DEVICE_BINFO * p_res, int msgtype, void * pdata)
p_res : the DEVICE_BINFO struct pointer
msgtype :
PROBE_MSGTYPE_MATCH - probe match
PROBE_MSGTYPE_HELLO - hello
PROBE_MSGTYPE_BYE - bye
note : if msgtype = PROBE_MSGTYPE_BYE, only p_res->EndpointReference field is
valid, the other fields is invalid
pdata : the user data

```

6. void set_monitor_cb(char * reference, int msgtype, onvif_probe_cb cb, void * pdata)

desc: Set the broadcast message (ProbeMatch, Hello, Bye) callback function for a specific device.

params:

reference : endpoint reference.

msgtype : message type, PROBE_MSGTYPE_MATCH, PROBE_MSGTYPE_HELLO or PROBE_MSGTYPE_BYE.

cb: the callback function point.

pdata: user data, when call backback pass back to user.

The callback function prototype please refer to set_ probe_ cb.

4.2 ONVIF Event API

The ONVIF Event API in onvif_event.h file.

1. BOOL onvif_event_init(uint32 http_srv_ip, uint16 http_srv_port, int max_clients)

desc: init event handler, init http server for receiving event notify messages

params:

http_srv_ip : http server listen ip address (network byte order), 0 means listening on all interfaces

http_srv_port : http server listen port

max_clients : max support client numbers

2. void **onvif_event_deinit()**

desc: uninit event handler

3. void **onvif_set_event_notify_cb**(onvif_event_notify_cb cb, void * pdata)

desc: set event notify callback

params:

cb: the callback function pointer, set cb to NULL, disable callback.

pdata: user data, when call backback pass back to user.

The callback function prototype is as follows:

void (* **onvif_event_notify_cb**) (Notify_REQ * p_req, void * pdata)

p_req: the notify message

pdata: the user data

4. void **onvif_set_subscribe_disconnect_cb**(onvif_subscribe_disconnect_cb cb, void* pdata)

desc: set event subscribe disconnect callback

params:

cb: the callback function pointer, set cb to NULL, disable callback.

pdata: user data, when call backback pass back to user.

The callback function prototype is as follows:

void (* **onvif_subscribe_disconnect_cb**) (ONVIF_DEVICE * p_dev, void * pdata)

p_dev: the onvif device pointer

pdata: the user data

4.3 System API

1. int **log_init**(const char * log_fname)

desc: open log file

params:

log_fname: log file name.

return: 0-success, -1-failed

```
2. int log_time_init(const char * fname_prev)
desc: open log file with timestamp
params:
    fname_prev: log file name prefix. Such as :
    log_time_init( " log " ); // The format of the generated log file is
    log-XXXXXXXX-XXXXXX.txt
return: 0-success, -1-failed

3. void log_set_level(int level)
desc: set log level
params:
    level: log level, as the following:
    HT_LOG_TRC
    HT_LOG_DBG
    HT_LOG_INFO
    HT_LOG_WARN
    HT_LOG_ERR
    HT_LOG_FATAL

4. void log_close()
desc: close log file

5. BOOL sys_buf_init(int nums)
desc: allocate systems buffer
params:
    nums: the number of system buffer allocated, each system buffer size is 2048
    bytes
```

NOTE: The allocated system buffer size is generally the maximum number of supported devices multiplied by 10.

The ONVIF CLIENT library allocates a piece of memory to receive and parse network data, so there is no need to dynamically allocate memory.

return: TRUE-success, FALSE-failed

6. void **sys_buf_deinit()**

desc: free systems buffer

7. BOOL **http_msg_buf_init(int num)**

desc: allocate http message parser buffer

params:

nums: the number of system buffer allocated, each http parser buffer size
is about 300 bytes

8. void **http_msg_buf_deinit()**

desc: free http message parser buffer

4.4 ONVIF Client API

The ONVIF client API in onvif_cln.h file.

All ONVIF CLIENT APIs comply with ONVIF standard documentations, for details
on the interfaces, please refer to the ONVIF standard documents:

<https://www.onvif.org/profiles/specifications/>

The API in onvif_api.h file is a simplified version of some commonly used API
interfaces.

ONVIF Application Programmers Guide :

https://www.onvif.org/wp-content/uploads/2016/12/ONVIF_WG-APG-Application_Programmers_Guide-1.pdf

Chapter 5 Example

Onvif client library usage examples please refer OnvifTest.cpp, OnvifTest2.cpp and OnvifTest3.cpp files.

Onviftest.cpp : Automatically discover onvif devices and perform test steps.

OnvifTest2.cpp : Manually add devices, get device information and subscribe events.

OnvifTest3.cpp : Thread version of OnvifTest2.cpp.